
FRONT COURT™

Page 1 of 3

CLASSIFICATION:

- Water-Dispersed/Acrylic Urethane Gym Finish

SCOPE:

- **Front Court** is a one-part water-dispersed, acrylic/urethane finish.
- The formulation of **Front Court** provides an extremely tough, high acrylic/urethane finish for sports floors and other hard floors.
- **Front Court** is safer for the environment with a VOC content less than 240 grams per liter, well below the industry standard.

USAGE:

Directions for use:

New or Sanded Wood Floors:

Wet floors are slippery. Prevent pedestrian traffic with wet floor signs or barricades.

NOTE: Avoid applying on extremely hot and humid days or when the inside floor temperature is below 70°F. Never apply **Front Court** to a floor that has been chemically stripped. Never apply to a bare wood floor. Always apply two coats of **Ecolab oil based sealer** first. The floor must be sanded completely to remove all old finish. Wear non-marking, soft-soled shoes.

1. Apply three coats of **Front Court** at 400 - 700 sq. ft. per gallon using the recommended applicator.* Work steadily without stopping, feathering as you go, until the entire coat is applied.
2. Allow **Front Court** to dry.
3. Release to light traffic after 24 hours and heavy traffic after 48 hours.
4. Do not use detergents or other cleaners on the floor (except for **Huntolene Dust Mop Treatment**) for 14 days.
5. Do not cover floor for 30 days.

Recoating Procedure for Previously Coated Floors:

Prevent pedestrian traffic with “Wet Floor” signs or barricades.

NOTE: Ecolab shall not be liable for any damages resulting from failure of this product due to improper floor preparations or seal applications.

1. Remove all soil. Wear soft-soled, non-marking gym shoes.
2. Screen with 60-100 grit screens until floor is uniformly dull. Remove any swirl caused by screens with sequential “fine” screens (100, 120 grit).
3. Before tacking, be sure doors are locked and air movement (fan) is turned off.
4. Sweep and vacuum all dust from floor.
5. Tack floor with water-dampened turkish towels, **tightly wrung out**, until floor is dust-free.
6. Allow floor to dry completely.
7. If floor is not being painted, skip to step #14.
8. If floor is being painted, tape lines and keys. Paint floor and allow to dry according to paint manufacturer’s recommendations.
9. Dry screen-painted areas to a uniform dullness with a grit screen to remove all paint luster (worn 100 or 150 grit screen).
10. Vacuum the paint dust from the floor.

USAGE:**Directions for use:**

11. Repeat steps #3, #5 and #6.
12. Tack painted area with **Seal-O-Solv**. Allow floor to dry.
13. Tack entire floor by repeating steps #3, #5 and #6.
14. Apply two coats **Front Court** at 400 - 700 sq. ft. per gallon using recommended applicator.* work steadily with out stopping, feathering as you go, until entire coat is applied.
15. Allow to dry. **Do not exceed 16 hours (between coats) prior to recoating or screening will be necessary.**
16. Release to light traffic after 24 hours and heavy traffic after 48 hours.
17. Do not use detergents or other cleaner on the floor (except **Huntolene Dust Mop Treatment**) for 14 days.
18. DO NOT cover floor for 30 days.

Applicator:

Apply **Front Court** with shortnap synthetic lambs wool pad on wooden block (use the snow plow method) at 400 - 700 sq. ft. per gallon.

CHEMICAL PROPERTIES:

- | | | |
|-----------------------------|-------------------------------------|------------|
| • Compositional Information | Diethylene Glycol Monoethyl Ether | 11-90-0 |
| | Polyurethane | 70131-70-3 |
| | Polymer Acrylic | ND |
| | Water | 7732-18-5 |
| • pH | 8.0 - 9.6 | |
| • VOC | less than 240g/L | |
| • Specific Gravity | 1.045 | |
| • Initial Boiling Point | >212°F | |
| • Solubility in Water | Mixes with water in all proportions | |
| • Solids | 30% ± 2% | |

PHYSICAL PROPERTIES:

- | | |
|--------------|--------------|
| • Appearance | Milky white |
| • Fragrance | Mild solvent |
| • State | Liquid |

ENVIRONMENT & SAFETY:

- | | | | |
|-----------------|------------|----------|----------------|
| • Hazard Rating | Health - 1 | Fire - 0 | Reactivity - 0 |
|-----------------|------------|----------|----------------|

STABILITY & STORAGE:

- Stable under normal conditions of handling.

FIRST AID:

- **Eyes** - Flush immediately with plenty of cool running water. Remove contact lenses, if used, and then flush again.
- **Skin** - Flush skin with water, then wash with soap and water. Remove contaminated clothing and wash before reuse.

FIRST AID (Cont.):

- **If swallowed** - Rinse mouth; then drink 1 or 2 large glasses of water. **DO NOT** induce vomiting. Never give anything by mouth to an unconscious person.

IF IRRITATION OR DISCOMFORT PERSISTS, CALL A PHYSICIAN.

PACKAGING & PRODUCT NUMBERS:

Size Available	Product Number
5 gal.	61110425
4/1 gal.	61110513

PROFESSIONAL PRODUCTS DIVISION

Ecolab Inc., 370 Wabasha Street, St. Paul, MN 55102 U.S.A.
5105 Tomken Road, Mississauga, Ont. Canada L4W2X5
www.ecolab.com 1-800-451-7191

