

# SHOWCASE

---

**CLASSIFICATION:**

- Oil-Modified Wood Floor Finish and Sealer

---

**SCOPE:**

- **Showcase** is a high-tech sealer finish that produces a rich luster on any wood floor. Easy to apply, offers superior leveling and quick dry time meaning less waiting. With great adhesion between coats, it is ideal for multi-coat applications.

---

**USAGE:****FOR INDUSTRIAL USE ONLY - NOT FOR HOUSEHOLD USE**

Apply *Showcase* using the *E-Z Way* applicator, T Bar, or conventional pan and block method at the rate of 500 square feet per gallon (12.3 m<sup>2</sup>/L). Wet floors are slippery. Prevent pedestrian traffic with wet floor signs or barricades.

**New/Sanded or Chemically Stripped Wood Floors:**

**Note:** All old finish must be removed from a sanded or chemically stripped floor. Wear non-marking soft-soled "gym" shoes.

1. Before tacking, be sure doors are locked and air movement is turned off.
2. Sweep and vacuum dust from floor. Do not use treated dust mops. Floor dust is combustible. Remove it from vacuums and all containers.
3. Tack floor with **Seal-O-Solv** dampened turkish towels **tightly wrung out**. Repeat until floor is dust free.
4. Allow floor to dry completely.
5. Apply **Showcase** using one of the applicators below\*. Work steadily without stopping, feathering as you go until the entire coat is applied.
6. Allow **Showcase** to dry 24 hours (longer if humidity is greater than 70%). Screen entire floor with medium grit screen (100) until **Showcase** is uniformly dull.
7. Tack floor by repeating steps #1-4.
8. Apply second coat of **Showcase** using the method in step #5.
9. Allow **Showcase** to dry 24 hours. Screen entire floor with a medium grit screen (100) until **Showcase** is uniformly dull.
10. Tack floor by repeating steps #1-4.
11. Tape lines and keys for painting according to paint manufacturer's recommendations.
12. Dry screen painted area with a grit screen aggressive enough to remove all paint luster to a uniform dullness (150 or worn 100 grit screen). This must be done to avoid peeling of the finish from the paint.
13. Tack floor by repeating steps #1-4.
14. Apply a third coat of **Showcase** using the method in step #5.
15. Allow **Showcase** to dry 24 hours. Screen entire floor with a medium grit screen (100) until **Showcase** is uniformly dull.
16. Tack floor by repeating steps #1-4.
17. Apply a fourth coat of **Showcase** using the same method as in step #5. †

**Recoating Procedure for Previously Coated Floors:**

1. Remove **all** soil. Wear non-marking soft-soled "gym" shoes. Check for wax, gum, or other substances.
2. Screen entire floor with medium (100) grit screen until floor is uniformly dull. Remove any swirls caused by medium screens with fine (150) screens.
3. Allow floor to dry completely.
4. Apply **Showcase** using one of the applicators below.\* Work steadily without stopping, feathering as you go until entire coat is applied.
5. If more than one coat is desired, allow to dry 24 hours (longer if humidity is greater than 70%). Screen entire floor with medium grit (100) screen until **Showcase** is uniformly dull.
6. Tack floor by repeating steps #3-6.
7. Apply second coat of **Showcase** using the method as in step #7. †

† Maximum hardness is not reached for several days; therefore, the following guidelines may be used. Light traffic after three days, heavy traffic after seven days. Avoid applying on extremely hot and humid days or when floor temperature is below 70°. Do not use detergents or other cleaners (except *Huntolene Dust Mop Treatment*) for 14 days. Do not cover floor with plastic sheeting, red resin paper or anything similar that will regard the curing process. Let the floor cure 30 days with good drying conditions before covering.

**IMPORTANT:** Do not store partially full containers of seal for long period of time. Do not pour unused material back into containers. Keep container tightly closed when not in use. Pour unused seal portion into properly marked, smaller metal container. Fill to top. Air will cause skinning, congealing and spoiling. Do not mix with other floor seals or finishes.

**Maintenance:** Sweep floor daily with *Huntolene* treated dust mop.

The Volatile Organic Compound (VOC) content of this product does not exceed 350 grams per liter.

The product is not for sale or use in the state of California.

**For service or additional information, call 1-800-35-CLEAN (352-5326).**

---

#### PHYSICAL AND CHEMICAL PROPERTIES:

- |                             |                         |            |
|-----------------------------|-------------------------|------------|
| • Compositional Information | Modified Alkyd Resin    | 68038-49-3 |
|                             | Mineral Spirits         | 64742-47-8 |
|                             | Silicone                | 556-67-2   |
|                             | Regular Mineral Spirits | 64741-41-9 |
|                             | Xylene                  | 1330-20-7  |
|                             | Ethylbenzene            | 100-41-7   |
| • Physical State            | Liquid                  |            |
| • Color                     | Amber                   |            |
| • Odor                      | Hydrocarbon             |            |
| • pH                        | NA                      |            |
| • Relative density          | 0.91                    |            |
| • Solids                    | 50%                     |            |

---

#### ENVIRONMENT & SAFETY:

- |                 |            |                  |                      |
|-----------------|------------|------------------|----------------------|
| • Hazard Rating | Health - 2 | Flammability - 2 | Physical hazards - 0 |
|-----------------|------------|------------------|----------------------|

---

#### HANDLING & STORAGE:

- Handling: Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray or mists. Keep away from heat, sparks and flame. To avoid fire, eliminate ignition sources. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
- Storage: Keep out of reach of children. Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Store between the following temperatures: -5 and 35°C

**KEEP OUT OF REACH OF CHILDREN**

**WARNING:** COMBUSTIBLE LIQUID AND VAPOUR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. Can cause central nervous system (CNS) depression. HARMFUL OR FATAL IF SWALLOWED. ASPIRATION HAZARD. CAN ENTER LUNGS AND CAUSE DAMAGE. CONTAINS TOXIC MATERIAL. Wear suitable gloves and eye protection. Use only with adequate ventilation. Avoid breathing vapours, spray or mists. Keep away from heat, sparks and flame. Wash thoroughly after handling.

**FIRST AID**

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water. Remove contact lenses and flush again. Get medical attention if irritation persists.

**Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if irritation persists. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**Inhalation:** If inhaled, remove to fresh air. If exposed person is not breathing, give artificial respiration or oxygen applied by trained personnel. Get medical attention if irritation persists.

**Ingestion:** If material has been swallowed and the exposed person is conscious, give small quantities of water to drink.

Do not induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately.

**READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.  
FOR EMERGENCY MEDICAL INFORMATION IN USA OR CANADA, CALL 1-800-328-0026.  
FOR EMERGENCY MEDICAL INFORMATION WORLDWIDE, CALL 1-651-222-5352 (IN USA).**

**PACKAGING & PRODUCT NUMBERS:**

Size Available	Product Number
5 U.S. gal / 18.9 L	61010163

**Ecolab Inc.**

370 Wabasha Street, St. Paul, MN 55102 U.S.A.  
5105 Tomken Road, Mississauga, Ont. Canada L4W2X5  
[www.ecolab.com](http://www.ecolab.com)

